

## Terminal Block for Printed Circuit Boards AK 700-BR

### Market Applications:

- Lighting Industry
- Any kind of earthing

### Our Advantages:

- 3-pole blocks, alignable via dove tails
- Wire size up to 4 mm<sup>2</sup> solid/ 2,5 mm<sup>2</sup> flexible with ferrules
- Pollutant free according RoHS/ WEEE
- Internally connected poles according DIN EN 61347-1



### Technical Data:

Rated Voltage	300 V	250 V
Rated Current	20 A	24 A (T60)
Wire Size	AWG 30-12	2,5 mm <sup>2</sup>
Test Voltage		2,0 kV
Rated Torque/ Screw Size		0,5 Nm/ M3

### Similar Competitor's Products:

- Phoenix Contact MKDS 3/..-B-5,08-GNYE
- Sauro MSQ..001-000C

### Exemplary Odering Code:

AK700/3-5.0-V-GREEN-BR

PTR Messtechnik GmbH & Co.KG  
 Gewerbehof 38 · D-59368 Werne  
 P.O. Box 14 62 · D-59357 Werne  
 Phone +49 (0) 23 89/ 79 88 - 0  
 Fax +49 (0) 23 89/ 79 88 - 88  
 e-mail: info@ptr.eu  
 http://www.ptr.eu

No liability can be accepted for any errors or incomplete data. This product information replaces all earlier editions. We reserve the right to make any changes which are in the interest of technical improvement. 08/08

